




0957



CAMTECH

**Showroom & Head Office: 21 Jarman Way
Royston, Herts
SG8 5HW**

16

0957-CPR-0608

100% Dark Pacaya Handmade
NEN-EN 771-1, April 2013, and NEN-EN 771-1/A1, March 2005
Category I, HD clay bricks
Production Reference code: Caprice DCMRZW-B

| | |
|--|---|
| Length: | 215 mm, T2 (+/- 4 mm), R1 (9 mm) |
| Width: | 102 mm, T2 (+/- 3 mm), R1 (6 mm) |
| Thickness: | 65mm, T2 (+/- 2 mm), R1 (5 mm) |
| Appearance: | Handmade/Stock/Waterstruck with frog (<20% of the volume), Euro group 1 |
| Average compressive strength: | >15 N/mm ² |
| Dimensional stability: | NPD |
| Bond strength: | Mean. 0.15 N/mm ² |
| Active soluble salts: | S2 |
| Reaction to fire: | Euro class A1 |
| Water absorption: | <23% m/md |
| Initial rate of water absorption: | IW4 strong suction, >4.0kg/m ² .min |
| Water vapour diffusion coefficient: | 5/10 |
| Gross dry density: | 1495 kg/m ³ , D1 (10%, +/- 155 kg/m ³) |
| Thermal conductivity: | 0,37 W/mK |
| Freeze/thaw resistance: | F2 |